



共通仕様	
精度等級	JIS N8級(旧JIS4級)
歯形	並歯
圧力角	20°
材 料	S45C相当

形状: B

※黒染処理は施していません

カタログ品番	モジュール	歯数	形状	基準円直径 PCD	歯先円直径 OD	ボス径 BD	歯幅 W	ボス長さ BW	ボス全長 BL	穴径 d	質量 kg
<b>MSB2.5-12</b>	モジュール 2.5	12	B	30	35	23	25	12	37	10	0.16
<b>MSB2.5-13</b>		13	B	32.5	37.5	25	25	12	37	10	0.19
<b>MSB2.5-14</b>		14	B	35	40	25	25	12	37	10	0.21
<b>MSB2.5-15</b>		15	B	37.5	42.5	30	25	12	37	13	0.24
<b>MSB2.5-16</b>		16	B	40	45	32	25	12	37	13	0.28
<b>MSB2.5-17</b>		17	B	42.5	47.5	35	25	12	37	13	0.33
<b>MSB2.5-18</b>		18	B	45	50	38	25	12	37	13	0.38
<b>MSB2.5-19</b>		19	B	47.5	52.5	39	25	12	37	13	0.42
<b>MSB2.5-20</b>		20	B	50	55	40	25	12	37	13	0.46
<b>MSB2.5-21</b>		21	B	52.5	57.5	42	25	12	37	13	0.51
<b>MSB2.5-22</b>		22	B	55	60	44	25	12	37	13	0.57
<b>MSB2.5-23</b>		23	B	57.5	62.5	46	25	12	37	13	0.62
<b>MSB2.5-24</b>		24	B	60	65	48	25	12	37	13	0.68
<b>MSB2.5-25</b>		25	B	62.5	67.5	50	25	12	37	13	0.75
<b>MSB2.5-26</b>		26	B	65	70	55	25	12	37	13	0.84
<b>MSB2.5-27</b>		27	B	67.5	72.5	60	25	12	37	13	0.94
<b>MSB2.5-28</b>		28	B	70	75	60	25	12	37	13	0.99
<b>MSB2.5-29</b>		29	B	72.5	77.5	62	25	12	37	13	1.06
<b>MSB2.5-30</b>		30	B	75	80	65	25	12	37	13	1.15
<b>MSB2.5-32</b>		32	B	80	85	70	25	12	37	13	1.32
<b>MSB2.5-34</b>		34	B	85	90	70	25	12	37	13	1.44
<b>MSB2.5-35</b>		35	B	87.5	92.5	70	25	12	37	13	1.51
<b>MSB2.5-36</b>		36	B	90	95	70	25	12	37	13	1.58
<b>MSB2.5-38</b>		38	B	95	100	70	25	12	37	18	1.68
<b>MSB2.5-40</b>		40	B	100	105	70	25	12	37	18	1.83
<b>MSB2.5-42</b>		42	B	105	110	70	25	12	37	18	2
<b>MSB2.5-44</b>		44	B	110	115	70	25	12	37	18	2.16
<b>MSB2.5-45</b>		45	B	112.5	117.5	70	25	12	37	18	2.24
<b>MSB2.5-46</b>		46	B	115	120	70	25	12	37	18	2.33
<b>MSB2.5-48</b>		48	B	120	125	70	25	12	37	18	2.51
<b>MSB2.5-50</b>		50	B	125	130	70	25	12	37	18	2.7
<b>MSB2.5-52</b>		52	B	130	135	70	25	12	37	18	2.9
<b>MSB2.5-54</b>		54	B	135	140	70	25	12	37	18	3.1
<b>MSB2.5-55</b>		55	B	137.5	142.5	70	25	12	37	18	3.22
<b>MSB2.5-56</b>		56	B	140	145	70	25	12	37	18	3.32
<b>MSB2.5-58</b>		58	B	145	150	70	25	12	37	18	3.53
<b>MSB2.5-60</b>		60	B	150	155	70	25	12	37	23	3.75
<b>MSB2.5-62</b>		62	B	155	160	80	25	12	37	23	4.3
<b>MSB2.5-64</b>		64	B	160	165	80	25	12	37	23	4.54
<b>MSB2.5-65</b>		65	B	162.5	167.5	80	25	12	37	23	4.62
<b>MSB2.5-66</b>		66	B	165	170	80	25	12	37	23	4.65
<b>MSB2.5-68</b>		68	B	170	175	80	25	12	37	23	4.92
<b>MSB2.5-70</b>		70	B	175	180	80	25	12	37	23	5.1
<b>MSB2.5-72</b>		72	B	180	185	80	25	12	37	23	5.28
<b>MSB2.5-75</b>		75	B	187.5	192.5	80	25	12	37	23	5.53
<b>MSB2.5-76</b>		76	B	190	195	80	25	12	37	23	5.9
<b>MSB2.5-80</b>		80	B	200	205	80	25	12	37	23	6.5

※ご要望に応じた、軸穴加工、キー加工、止めねじ加工を承ります。別途、お問い合わせください。