



形状: B

共通仕様	
精度等級	JIS N8級(旧JIS4級)
歯形	並歯
圧力角	20°
材料	S45C相当

※黒染処理は施していません

カタログ品番	モジュール	歯数	形状	基準円直径 PCD	歯先円直径 OD	ボス径 BD	歯幅 W	ボス長さ BW	ボス全長 BL	穴径 d	質量 kg
MSB6-12	モジュール 6	12	B	72	84	55	60	28	88	23	2.12
MSB6-13		13	B	78	90	58	60	28	88	23	2.51
MSB6-14		14	B	84	96	60	60	28	88	23	2.91
MSB6-15		15	B	90	102	70	60	28	88	23	3.52
MSB6-16		16	B	96	108	75	60	28	88	23	4.06
MSB6-17		17	B	102	114	78	60	28	88	23	4.58
MSB6-18		18	B	108	120	80	60	28	88	23	5.11
MSB6-19		19	B	114	126	90	60	28	88	23	5.9
MSB6-20		20	B	120	132	100	60	28	88	23	6.74
MSB6-21		21	B	126	138	105	60	28	88	26	7.38
MSB6-22		22	B	132	144	110	60	28	88	26	8.14
MSB6-23		23	B	138	150	115	60	28	88	26	8.93
MSB6-24		24	B	144	156	120	60	28	88	26	9.76
MSB6-25		25	B	150	162	125	60	28	88	26	10.63
MSB6-26		26	B	156	168	130	60	28	88	26	11.53
MSB6-27		27	B	162	174	135	60	28	88	26	12.43
MSB6-28		28	B	168	180	140	60	28	88	26	13.44
MSB6-30		30	B	180	192	150	60	28	88	28	15.5
MSB6-32		32	B	192	204	150	60	23	83	28	16.4
MSB6-34		34	B	204	216	150	60	23	83	28	18.2
MSB6-35		35	B	210	222	150	60	23	83	28	19
MSB6-36		36	B	216	228	150	60	23	83	28	20
MSB6-38		38	B	228	240	150	60	23	83	28	22
MSB6-40		40	B	240	252	150	60	23	83	28	24
MSB6-42		42	B	252	264	150	60	23	83	38	26
MSB6-44		44	B	264	276	150	60	23	83	38	28.3
MSB6-45		45	B	270	282	180	60	23	83	38	30.7
MSB6-46		46	B	276	288	180	60	23	83	38	32.1
MSB6-48		48	B	288	300	180	60	23	83	38	34.5
MSB6-50		50	B	300	312	180	60	23	83	38	37.2

※ご希望に応じた、軸穴加工、キー加工、止めねじ加工を承ります。別途、お問い合わせください。